



K80 - TORNADO PRINTER

80mm ticket / receipt printer

- 200dpi best printing quality
- Paper width from 76 to 80mm
- Paper roll (diameter 180mm on board)
- RS232 and USB interface
- 1D/ 2D barcodes printing capability (QR CODE)
- International fonts on board: any language available
- Highly reliable cutter
- Sensors: Head temperature, paper presence, near paper end, black mark 6 position, ticket out



CHARACTERISTICS

Ideal solution for ATM's VTM's & Self Service Kiosk

- Ultra-compact
- Heavy-duty alluminium printing engine
- Anti-jamming system
- Anti-instrusion shutter
- Anti-splash paper exit
- On/off switch

AVAILABLE VERSIONS

- K80 - TORNADO PRINTER: With output paper mouth, anti intrusion shutter and ticket sensor, low paper level sensor for roll up to 180mm
 - K80 - PRINTING KIT: kit including printer mechanism, cutter & board, ideal for queue management
-

ACCESSORIES

- Near paper end sensor for paper roll exceeding 180mm

What is in the box:

- Device, locking ring
-

TECHNICAL SHEET


| | |
|------------------------|--|
| Printing Method | Thermal, fixed head |
| Number of dots | 8 dot/mm |
| Resolution | 203 dpi |
| Printing (mm/sec) | 150 mm/s |
| Character set | 54 character code tables Extended chinese GB18030-2000, Korean PC949 |
| Supported Barcode | UPCA, UPCE, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, QRCODE |
| Printing Format | Height/Width from 1 to 8, bold, reverse, underlined, italic |
| Printing Direction | Normal, 90°, 180°, 270° |
| Paper width | 76, 80 ± 0,5 mm |
| Paper weight | from 55 g/m2 to 80 g/m2 |
| Paper thickness | from 63 μ m to 88 μ m |
| Printing width | from 52 to 80mm |
| Roll Dimension | max 180 mm |
| Sensors | Head temperature, paper presence, near paper end, black mark, ticket out |
| Emulation | CUSTOM/POS |
| Interfaces | USB + RS232 Serial |
| Data Buffer | 8 Kbytes |
| Flash Memory | 768 Kbytes internal, 4 Mbytes external |
| RAM Memory | 128 Kbytes |
| Graphic Memory | 1 logo (640x409 dots) |
| Drivers | Windows [®] (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit); Android [™] ; iOS |
| Software Tools | PrinterSet, CustomPowerTool, Custom Windows API |
| Power supply | 24 Vdc ±10% (optional external power supply) |
| Medium consumption | 0.8 A (12,5% dots on) |
| MTBF | 165 245 hours (electronic board) |
| Head Life | 100 Km |
| MCBF | 1.000.000 cut |
| Operating temperature | from 0°C to +50°C |
| Dimensions | 258(L) x 103.5(H) x 135(W) mm |
| Weight | 1250 g |

MODELS



915LC011100300

PRINTER K80 USB RS232
SHUT+NOTCH+MOUTH



976LC010000001

KIT MECHANISM + CUTTER +
BOARD K80

Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice.

Last update: 23 May 2023