



VALUESCAN III

AUTO-SENSOR 1D BARCODE READER

KEY FEATURES:



- Scanning range up to 12 inches from barcode
- Auto-sensing mode allows operation while scanner is in its stand; LED indicator
- Symbologies:
 - Aviation25
 - China Post
 - Codabar
 - Code 11
 - Code 32 (Italian)
 - Code 39
 - Code 39 Full ASCII
 - Code 93
 - Code 128
 - EAN-8
 - Extended
 - GS1 Limited
 - GS1-128 & ITF-14
 - GS1 Omnidirectional
 - Industrial 2 of 5
 - Interleave 2 of 5
 - ISBN
 - ISSN
 - Matrix 2 of 5
 - MSI
 - Plessey
 - SISASI & RSS14
 - UPC-A
 - UPC-E



VALUESCAN III SPECS

APPROVALS	BSMI, CE & FCC
DIMENSIONS	102mm (L) x 177mm (W) x 71mm (D)
DROP TEST	1.5m
HUMIDITY	5% to 95% Non-Condensing
IMAGE SENSOR	CMOS 1280 x 800
INTERFACE	USB-HID & USB Virtual COM
LIGHT SOURCE	RED LED 620nm - 630nm
OPERATING TEMPERATURE	-20°C to 50°C
POWER	5.0 VDC +/- 10%
PROCESSOR	1GHz, X1500
RANGE	350mm +/- 50mm
SCAN RATE	270 Times per Second
STORAGE TEMPERATURE	-40°C to 70°C
WEIGHT	190g



CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
T: (714) 761-6368
TF: (800) 984-1010
F: (714) 761-8880
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368
SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED

IDTECH®

Value through Innovation

IDTECHPRODUCTS.COM

