



# 6553L 65-inch

Touchscreen Signage



**Integrated Touch**



**Commercial Grade**



**3-Year Warranty**

## Product Overview

Elo's 6553L 65-inch interactive digital signage touchscreen delivers a professional-grade large format display in a slim, integrated package. With a 500 nit LED panel, the 6553L is a bright, high quality display suitable for public environments. State of the art HD display technology is utilized including a high contrast/brightness LED-backlit LCD panel, extended color gamut with movie/ gaming/ photo modes, black level adjustment, and on-screen menu enhancements.

Available with Elo's industry leading TouchPro® Projected Capacitive (PCAP) enabling up to 40 touches or Infrared (IR) touch technology with up to 20 touches. Both touch technologies provide a fast and extremely sensitive response that are compatible with Microsoft Windows® 7, Windows 10 and Android 7.1 operating systems. Additionally, the PCAP display provides the optimal large format, "smart phone like" touch experience with edge-to-edge glass aesthetics that is easy to clean with no edges to trap dirt and grease.

**The 2 inches (51 mm) thin (<4" mounted) design is compliant with ADA and IBC protrusion requirements**

**Reliable, integrated IDS solution with optional peripherals and webcam kits**

**Optional, high-performance computer modules are available to turn the IDS 02-Series displays into completely integrated all-in-one computers**

## 6553L 65" Touchscreen Signage

Specifications	
Model	6553L
Form Factor	Digital Signage
Color	Black
Active Display Area (W x H)	56.2" x 31.6" (1428.48 mm x 803.52 mm)
Dimensions (W x D x H)	TouchPro: 58.69" x 34.08" x 3.17" / 1490.6 mm x 865.5 mm x 80.4 mm; IR: 58.69" x 34.07" x 3.55" / 1490.6 mm x 865.5 mm x 90.2 mm
Display Technology	3840 x 2160 @ 60hz (native); Active matrix TFT LCD with LED backlight (Other resolutions supported)
Mounting Options	400mm x 400mm VESA 4-hole mounting interface on rear of unit
Diagonal Size	64.53" / 1639.06 mm
Aspect Ratio	16:9
Number of Colors	10 bit (D), 1.07 Billion
Brightness (typical)	LCD Panel 500 nits; with IR 450 nits; with TouchPro PCAP: 430 nits
Response Time (Tr + Tf) (typical)	8 msec
Viewing Angle (typical)	Horizontal: ±89°/178° total; Vertical: ±89°/178° total
Contrast Ratio (typical)	1100:1
On-Screen Display (OSD)	Let's Get Started, Video Source Select, Color Settings, Audio Settings, Power, Time, OSD Settings, Information, Conference
Available I/O Ports	Input: HDMI x2, USB 3.0 Type B, RJ45 OSD Remote, DisplayPort 1.4, 3.5mm TRS jack for Serial RS232 Output: 3.5mm Audio Headphones Line-out, RJ45 (for optional OSD remote) Side Accessible: HDMI x1, USB 3.0 Type A, Power Button, Video Source Selection, On Screen Display Button
Video Inputs	2x HDCP-capable HDMI on Type A connector, DisplayPort 1.4 connector Input Video Horizontal Sync frequency range: 121.8 - 140 KHz; Input Video Vertical Sync (frame rate) frequency range: 47 - 63 Hz
Power	IR: ON (monitor + AC/DC adapter): 152W, SLEEP (monitor + AC/DC adapter): 2W, OFF (monitor + AC/DC adapter): 0.7W TouchPro: ON (monitor + AC/DC adapter): 157W, SLEEP (monitor + AC/DC adapter): 2W, OFF (monitor + AC/DC adapter): 0.7W
Audio	Internal Speakers: 2 x 10 W stereo speakers; Input audio connector: 3.5 mm TRS jack; Input audio signal range: 1Vrms max stereo signal (standard PC line out); Headphone output connector: 3.5 mm TRS jack
Weight	(Unpackaged) TouchPro: With ECM: 115.54 lbs / 52.41 kg Without ECM: 111.14 lbs / 50.41 kg Without ECM: 114.13 lbs / 51.77 kg (Packaged) TouchPro: Without ECM: 131.04 lbs / 59.44 kg Without ECM: 136.24 lbs / 61.8 kg
Shipping Dimensions	68.9" x 45.28" x 11.02" / 1750 mm x 1150 mm x 280 mm
Maximum Operating Time	24 hours/day
Temperature	Portrait/Landscape Mode: Operating: 0°C to 40°C OR 32°F to 104°F; Storage: -20° C to 60° C OR -4°F to 140°F;
Humidity (non-condensing)	Operating: 20%-80%; Storage: 10%-95%
Regulatory Approvals and Declarations	UL, FCC; cUL, IC; CB; CE; RCM; VCCI; CCC (for TouchPro only)
Mounting Options	VESA MOUNT PER MIS-F, 400 x 400mm, M6; VESA MOUNT PER MIS-F, 600 x 600mm, M8
Warranty	3 years standard. On-site exchange (U.S. only)
Extended Warranty	4 year warranty coverage - Elo P/N: E446308 5 year warranty coverage - Elo P/N: E967470 3 year warranty coverage + AUR - Elo P/N: E967781 4 year warranty coverage + AUR - Elo P/N: E065005 5 year warranty coverage + AUR - Elo P/N: E065232 4 year warranty coverage + OSE (Continental US only) - Elo P/N: E065906 5 year warranty coverage + OSE (Continental US only) - Elo P/N: E898062
MTBF	50,000 hours demonstrated
What's in the Box	Infrared Model: QIG, HDMI 2.0 cable, USB 3.0 cable (Type A plug to Type B plug), power cable, IEC 60320-C13 to (NA plug, EU/KR plug, UK plug), Serial 3.5mm male to Serial DB9 female cable, Energy label according to EU Regulation 1062/2010, Passive Stylus x2 TouchPro Model: QIG, HDMI 2.0 cable, USB 3.0 cable (Type A plug to Type B plug), power cable, IEC 60320-C13 to (NA plug, EU/KR plug, UK plug), Serial 3.5mm male to Serial DB9 female cable, Energy label according to EU Regulation 1062/2010, Active Stylus x2

## Ordering Information

Model	Part Number	Technology	Surface Treatment	Touch Interface
6553L	E215638	Infrared	Anti-Glare	USB
	E215435	TouchPro PCAP	Anti-Glare	USB

## Optional Computer Modules

Model	Part Numbers	Processor	RAM	Storage	OS
ECMG4-i5	E400587	Intel Core i3-6100 Processor	4GB	128GB SSD	No OS
	E400775	Intel Core i3-6100 Processor	4GB	128GB SSD	Windows 7
	E400965	Intel Core i3-6100 Processor	4GB	128GB SSD	Windows 10
Elo Backpack™	E611864	Qualcomm® Snapdragon™ APQ8053 CPU	2GB	16GB eMMC	Android

To find out more about our extensive range of Elo touch solutions, go to [elotouch.com](http://elotouch.com), or call the office nearest you.

### North America

Tel +1 408 597 8000  
Fax +1 408 597 8050  
[elosales.na@elotouch.com](mailto:elosales.na@elotouch.com)

### Europe

Tel +32 (0)16 70 45 00  
Fax +32 (0)16 70 45 49  
[EMEA.Sales@elotouch.com](mailto:EMEA.Sales@elotouch.com)

### Asia-Pacific

Tel +86 (21) 3329 1385  
Fax +86 (21) 3329 1400  
[www.elotouch.com.cn](http://www.elotouch.com.cn)

### Latin America

Tel +52 55 2281 6958  
[elosales.latam@elotouch.com](mailto:elosales.latam@elotouch.com)

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo and the Elo logo are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.  
© 2019 Elo Touch Solutions, Inc. All rights reserved. 19062AES00124

