

## **Elo Access™ Self-Service Temperature Screening Solution**

Let Elo help simplify access control and visitor management with the modular Elo Access<sup>TM</sup> Temperature Screening solution. Utilizing an infrared bolometer and 2D camera, the Temperature Sensor Pro uses heatmap temperature reading technology - all in an easy to attach Elo Edge Connect accessory. The sensor can detect faces, automatically adjust based on height, and output temperature data for each person detected in the field of view (FOV). Simply pair Elo's Temperature Sensor Pro with a variety of displays, stands and 3rd-party software to create a self-service solution purpose-built to streamline security administration and increase safety.\*

By leveraging the Temperature Sensor SDK, partners can create seamless communication between their software and Elo hardware. And with EloView, you can deploy and securely manage your entire network of Elo Android-powered devices from anywhere.

Elo's Self-Service Stands are easily customizable. From branding and messaging to integrating a printer, payment device or a variety of camera options, Elo's modular platform has the flexibility and scalability businesses need.

EloView® users can also leverage the Elo Access App, a customizable questionnaire that's easy to deploy and allows companies to screen employees and visitors at entry to assess wellness related concerns.\*\*



With Elo's self-service solution, you can create a seamless experience.

st STEP

Greet individual instantly with facial detection

2<sup>nd</sup>
STEP

Automatically initiate temperature measurement

3rd STEP

Within seconds provide temperature reading results

## **Temperature Sensor Pro**

Specifications		
Part Number	E534879	
Interface	USB 2.0	
Measurement Accuracy	+/- 0.5 °C	
Scan Time	<1 second	
Measurement Distance	12" - 40" / 30cm - 102cm with optimal distance of 24" / 61cm	
Temperature Measurement Range	30 °C to 42 °C / 86 °F to 108 °F	
IR Camera Resolution	160 x 120	
RGB Camera Resolution	5MP	
Tilt Angle	+30°/-15° (auto or manual adjustment)	
IR FOV	36° (horizontal), 27° (vertical)	
RGB FOV	65°	
Display Compatibility	I-Series AiO for Android - 10", 15", 22" I-Series AiO for Windows - 15", 22" Touchscreen Monitors - 1002L, 1302L, 1502L, 1902L, 2002L, 2402L, 2702L Large Format Touchscreen Signage - 3202L, 4202L, 4602L, 5502L	
Temperature	Operating: 10° C to 40° C (50° F to 104° F); Storage: 0° C to 50° C (32° F to 122° F)	
Humidity (non-condensing)	Operating: 20% - 80%; Storage: 10% - 90%	
OS Support	SDKs available for Elo's Android and Windows devices	
Warranty	2-year standard warranty	
What's in the Box	Temperature Sensor, 2 Mounting screws, 2 Mylar screw covers, QIG	

## **Create Your Solution**

Specifications	
Display Sizes	AiO Interactive Displays - 10", 15" and 22" I-Series Android / 15" and 22" I-Series Windows Touchmonitors - 1002L, 1302L, 1502L, 2002L, 2402L, 2702L Large Format Interactive Displays - 3202L, 4202L, 4602L, 5502L
Self-Service Stands	Wallaby Self-Service Stands (Countertop & Floor) Slim Self-Service Stands (Countertop & Floor)
Other Accessories	POE (only available for I-Series for Android), EMV Cradles, MSR, 1D & 2D Barcode Scanners, MSR, Fingerprint Reader, Status Light, NFC, Customer-facing Displays

## **Ordering Information**

Part Number	Description
E534879	Temperature Sensor Pro

Learn more about Elo at **EloTouch.com**.

mericas Europe (EMEA)

Tel +1 408 597 8000 Tel +32 (0)16 70 45 00 elosales.na@elotouch.com EMEA.Sales@elotouch.com

**Asia Pacific** 

Tel +86 (21) 3329 1385 www.elotouch.com.cn

\*The Elo Access Temperature Sensor is not intended to diagnose, treat, cure, mitigate, or prevent any disease or health condition, including COVID-19. An indication of an elevated body temperature should be confirmed by a secondary evaluation method (such as a non-contact infrared thermometer or clinical grade contact thermometer). Use only as directed; various environmental and methodological factors can impact thermal imaging. HIPAA compliance is responsibility of user. This is not an FDA-approved device. Not available in all areas.

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, Elo Edge Connect and Wallaby are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2020 Elo Touch Solutions, Inc. All rights reserved. 20073AES00139



<sup>\*\*</sup>Screening questions for the Elo Access App are the responsibility of the user, who must confirm compliance with applicable data privacy, medical data privacy, and employment laws and regulations, including HIPAA compliance. Not available in all areas.