

## DATA SHEET CR2100



# CODE READER 2100



### Expect More

- High-speed, multidirectional reading of 1D and 2D barcodes
- QuickConnect to host PC via base station, dongle, or DirectConnect
- Bluetooth® 5 Low Energy enhances data security and extends battery life
- Visual, audible, and haptic feedback
- Batch mode stores data for later offload
- Smart battery with built-in power gauge for proactive management
- Compatible with Android, iOS, and Windows (via USB or Bluetooth)
- Swappable battery keeps business moving
- PVC-free CodeShield® plastics stand up to frequent cleaning
- Inductive charging eliminates potential charging contact failure caused by cleaners

### Common Applications



### Features at a Glance



### Uncanny scanning. More affordable than ever. Get data into your system of choice with a simple and reliable wireless workflow.

The CR2100 is one of Code's fourth-generation barcode readers, combining over twenty years of experience with features for improving the flow of information. We took unparalleled scanning performance and stepped it up a notch, tackling even more damaged and poorly printed barcodes to keep your business moving.

The CR2100 brings Bluetooth® 5 to your workflow, increasing the security level of your data transmissions. By implementing a Bluetooth Low Energy radio, Code has extended battery life—minimizing downtime during the workday. A built-in gauge tells users when it's time to change the battery, which can quickly be swapped for a fresh one, getting your team right back to work.

The Code Team is also ready to assist with installation and training options to ensure a smooth rollout. Among the most dependable barcode readers available, Code scanners maximize your uptime. Want to take that uptime to a new level? Code protection plans practically eliminate downtime.

With the introduction of wireless (inductive) charging, Code has eliminated any exposed metal. Combined with seamless construction, an IP52 rating and CodeShield® Level 1 plastics, the CR2100 can be quickly and completely wiped down.

**You know your unique business and Code knows barcode scanning. We're ready to help you implement the CR2100 to tackle your specific scanning needs and empower your team to keep moving.**

**Visit [codecorp.com](http://codecorp.com) to get in touch with your local Code team member.**

# DATA SHEET CR2100



## Accessories

- USB Charging Cables
- Power Supplies
- Batteries
- Bluetooth Inductive Charging Stations
- Desktop Mounts
- Wall Mount Brackets
- VESA Mount Brackets
- Precut Adhesive Tapes
- Thumb Screws
- Bluetooth® Dongles

## Typical Working Ranges

Test Barcode	Min Inches	Max Inches
7.5 mil Code 39	1.25" (32 mm)	6.4" (162 mm)
10.5 mil GS1 Databar	0.59" (15 mm)	5.75" (146 mm)
13 mil UPC	0.905" (23 mm)	10.0" (254 mm)
6.3 mil DM	1.10" (28 mm)	4.17" (106 mm)
10 mil DM	0.63" (16 mm)	6.46" (164 mm)
20.8 mil DM	0.83" (21 mm)	12.52" (318 mm)

Note: All samples were high-quality barcodes and were read along a physical center line at a 10° angle. Measured from the front of the read with default settings in metric units then converted to imperial units. Testing conditions may impact working ranges.

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by The Code Corporation is under license. Other trademarks and trade names are those of their respective owners.

## Physical Characteristics

Reader Dimensions	5.1" H x 2.1" W x 5.1" L (129 mm H x 52 mm W x 130 mm L)
Charging Station Dimensions	Charging Station: 1.9" x 3.1" W x 3.1" L (49 mm H x 79 mm W x 79 mm L) With base: 2.2" H x 3.7" W x 4.8" L (55 mm H x 93 mm W x 121 mm L)
Reader Weight	6.2 oz. (177 g) including battery
Charging Station Weight	3.4 oz. (97 g)
IP Rating	52
Colors	Black

## Performance Characteristics

Field of View	Single field: 50° horizontal by 33.5° vertical
Focal Point	Approximately 3.9" (100 mm)
Sensor	CMOS 1.2 megapixel (1280 x 960) grayscale
Optical Resolution	Single field: 960 x 640
Pitch	± 65° (from front to back)
Skew	± 60° from plane parallel to symbol (side-to-side)
Rotational Tolerance	± 180°
Symbol Contrast	15% minimum reflectance difference
Target Beam	Single blue targeting bar, 470 nm
Ambient Light Immunity	Sunlight: Up to 9,000 fc (96,890 lux)
Shock	Withstands multiple drops of 6' (1.8 m) to concrete
Power Requirements	Reader: 5 VDC; Charging station: 5 W max; Quad-bay charger: 6 W max
Number of Scans	Up to 50,000 scans per charge
ESD Protection	15 kV air, 8 kV direct
Charge Station Communication Interfaces	USB 2.0 (Generic HID, HID Keyboard, CDCS)
Reader Communication	Bluetooth® 5 Low Energy (Class II)
Warranty	Visit: <a href="http://codecorp.com/support/warranty">codecorp.com/support/warranty</a>

## User Environment

Operating Temperature	-4° to 131° F (-20° to 55° C)
Storage Temperature	-22° to 150° F (-30° to 65° C)
Humidity	5% to 95% non-condensing
Decode Capability	1D: BC412, Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, IATA 2 of 5, Interleaved 2 of 5, GS1 DataBar, Hong Kong 2 of 5, Matrix 2 of 5, MSI Plessey, NEC 2 of 5, Pharmacode, Plessey, Straight 2 of 5, Telepen, Trioptic, UPC/EAN/JAN Stacked 1D: Codablock F, Code 49, GS1 Composite (CC-A/CC-B/CC-C), MicroPDF, PDF417 2D: Aztec Code, Data Matrix, Data Matrix Rectangular Extension, Grid Matrix, Han Xin, Maxicode, Micro QR Code, QR Code, QR Model 1, Dot Code Proprietary 2D: GoCode® (optional license required) Postal codes: Australian Post, Canada Post, Intelligent Mail, Japan Post, KIX Code, Korea Post, Post-Net, Planet, UK Royal Mail, UPU ID-tags
Image Output Options	Formats: JPEG, BMP or PGM
Field of View	Wide field
Data Parsing	GS1, HIBC, driver's licenses & ID cards
Data Structure Validation	ISO15418, ISO15434, HIBC UDI