

AXIUM RX7000


Deliver value-added services in multilane retail stores with a smart and customizable commerce solution



- Manage high volume transactions with a smart POS designed for intensive use
- Deliver next-level customer experience with advanced services, from Buy now, Pay later to warranty contract and personalized loyalty programs
- Our implementation of the Android operating system brings a security layer that is compliant with PCI PTS and enables security updates
- The Axiom platform includes a full range of payment devices and APIs for easy integration of value-adding applications



- PCI compliant privacy pin shield



Connectivity	<ul style="list-style-type: none">• Wired• Wireless	<ul style="list-style-type: none">• Ethernet 10/100 base T• WiFi IEEE8.2.11 a/b/g/n 2.4G and 5G• Bluetooth 5.0, supports BLE	<div><div></div><div></div><div></div></div>
Connections	<ul style="list-style-type: none">• IDMI	<ul style="list-style-type: none">• Power• USB Host• USB Device• RS232• Ethernet	<div><div></div><div></div><div></div><div></div><div></div></div>
Data Capture	<ul style="list-style-type: none">• Front camera• Rear camera	<ul style="list-style-type: none">• 5M pixels , autofocus, for photo/video• 0.3 pixels, fixed focus camera, for bar code scanning	<div><div></div><div>Optional</div></div>
Privacy Shield	<ul style="list-style-type: none">• Standard privacy shield	<ul style="list-style-type: none">• PCI compliant	<div><div></div></div>
Stand Mounting	<ul style="list-style-type: none">• Universal Payment Mount		<div><div></div></div>
Size	<ul style="list-style-type: none">• Terminal only	<ul style="list-style-type: none">• 5.9 × 6.4 × 1.1" (151 × 163 × 27 mm)	<div><div></div></div>
Weight	<ul style="list-style-type: none">• Terminal only	<ul style="list-style-type: none">• 22.9oz (650 g)	<div><div></div></div>
Security	<ul style="list-style-type: none">• PCI• Overlay/skimmer detection• Anti-removal• Anti-theft	<ul style="list-style-type: none">• PCI PTS V6 compliant• Proximity sensor on surface of the keyboard*• Active connector removal• Kensington lock receptacle	<div><div></div><div>Optional</div><div></div><div></div></div>
Environment	<ul style="list-style-type: none">• Operating Temperature• Storage Temperature• Operating Humidity	<ul style="list-style-type: none">• 14°F to 122°F (-10°C to +50°C)• -4°F to 158°F (-20°C to +70°C)• 10% to 90% non-condensing	<div><div></div><div></div><div></div></div>
Accessories	<ul style="list-style-type: none">• Signature stylus• POE Box	<ul style="list-style-type: none">• Passive stylus + holder + cord• Power over Ethernet	<div><div>Optional</div><div>Optional</div></div>



ingenico