

SPECIFICATION SHEET

Mobilink[™] TM-P60II Mobile Wireless Receipt Printer with Auto Cutter



The portable 2" receipt printer.

Multi-platform printing — mPOS friendly; compatible with iOS[®], Android[™] and Windows[®] mobile devices; Zebra[®] emulation available for label applications

Long-life battery — operational up to 46 hours (Bluetooth[®]), or up to 27 hours (wireless)¹

Ultra fast — prints up to 100 mm/sec for receipts, 80 mm/sec for labels and 40 mm/sec in Peeler Mode

Rugged design - 4-foot drop rating and IP54 environmental certified

Easy wireless configuration — 802.11 a/b/g/n with 2.4 GHz/5 GHz compatibility, plus Bluetooth 2.1 (EDR supported); supports wireless security WEP, WPA and WPA2-Enterprise

Versatile - includes ESC/POS®, OPOS and JavaPOS™ drivers

Paper-saving options — reduce your paper usage by up to 23 percent

Compact design — weighs just 1.4 lb (receipt); 1.3 lb (label)

Comprehensive service and support — dedicated technical resource team and customized solutions; 1-year limited warranty

POS



Mobilink[™] TM-P60II Mobile Wireless Receipt Printer with Auto Cutter

Printing

Print Method Thermal line printing Print Speed

Receipt Mode: 100 mm/sec Label Mode: 80 mm/sec

Peeler Mode: 40 mm/sec Print Resolution Dot/line: 420/432 dots

Fonts Font A: 12 x 24, new Font B: 10 x 24, new Font C: 8 x 16

Column Capacity 58 mm paper, Font A/B/C, 35/42/52 columns; 60 mm paper, Font A/B/C, 36/43/54 columns Character Size 1.5 x 3.0 / 1.25 x 3.0 / 1.0 x 2.0 mm (W x H)

Character Set 95 Alphanumeric, 48 International, 128 x 10 Graphic

Characters per Inch 17/20/25 cpi

Barcode

1D: EAN-8, EAN-13, UPC-A, UPC-E, JAN13, JAN8, Code 39, Code 93, Code 128, ITF, CODEBAR, GS1-128, GS1 DataBar, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded

2D: QR Code, Maxi Code, PDF417, Composite, Data Matrix, RSS/GS1 and Aztec

Media Handling

Width

Receipt version: Paper or labels, 58 mm or 60 mm Label version: Paper or labels, 30 - 60 mm

Paper Loading Automatic label removal from backing (label version)

Core Diameter 51 mm

Auto Cutter Partial cut, left uncut (receipt version)

Bluetooth 2.1 + EDR Mobile Supported Operating Systems: Wireless (802.11): iOS, Android and Windows (Security Level WEP, WPA, WPA2-Enterprise), Bluetooth: iOS, Android and Windows Reliability 10 million printing lines; 500,000 auto cutter (receipt version) Drop Rating Test rating of 4 feet Charging AC adapter (2.5 hours to full charge), custom quad bay charger (2.5 hours to full charge) Battery Life Up to 27 hours with 802.11n, up to 46 hours with Bluetooth 2.1 + EDR Data Buffer 4,096 bytes Software TM-P60II Utility, EpsonNet Config, EpsonNet Simple Viewer, TM-P60II Remote Configuration Tool, TM Bluetooth Connector, Built-in Configuration Page Audible Alert Programmable buzzer LED Indicators Green LED: Power (ON=Power on, OFF=Power off) Orange LED: Only shown when power is ON; Error, Paper end, Cover open, Battery level low (printer does not operate) Blue LEDs: Four battery level indicators: 3 LED ON = approx. 100% - 60% 2 LED ON = approx. 60% - 20%1 LED ON = approx. 20% - 10%

Interfaces 802.11b/g/n (2.4 GHz) and 802.11a/n (5 GHz) or

1 LED Flashing = approx. 10% - 1% Sensors Paper out (receipt and label versions); gap, black

mark, label taken (label version)

Power Source Custom Lithium-Ion battery pack, AC adapter (option)

Temperature Operating: 0 °C to 45 °C Dimensions 4.05" x 6.25" x 2.55" (103 x 159 x 65 mm)

$(W \times D \times H)$ Weight

General

Receipt version: 1.4 lb (630 g) with battery, belt clip Label version: 1.3 lb (600 g) with battery, belt clip Color Epson Black

Warranty Standard with a 1-year limited warranty



What's in the Box

Mobilink TM-P60II, Battery (Model: OT-BY60II), Roll paper (for checking initial movement of the printer), User's manual, USB cable, Belt clip (already attached to printer), 58 mm spacer (already attached to printer)

Eco Features

RoHS compliant Recyclable product² Epson America, Inc. is a SmartWay® Transport Partner³

Ordering Information

Receipt Version	
Mobilink TM-P60II Wireless	C31CC79A9991
Mobilink TM-P60II Wireless	
no external power supply	C31CC79012
Mobilink TM-P60II Bluetooth	C31CC79A9901
Mobilink TM-P60II Bluetooth,	
no external power supply	C31CC79551
Label Version	
Mobilink TM-P60II Wireless	C31CC79A9931
Mobilink TM-P60II Wireless	
no external power supply	C31CC79312
Mobilink TM-P60II Bluetooth	C31CC79A9911
Mobilink TM-P60II Bluetooth	
no external power supply	C31CC79751
Battery	OT-BY60II
Quad charger	OT-CH60II
Power supply	PS-11
Shoulder strap and padded case	AB1370EPI

<u>Mobile Receipt Printers</u>

POS

1 Battery life can vary significantly depending on usage. | 2 For convenient and reasonable recycling options, visit www.epson.com/recycle | 3 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future eco.epson.com



Epson America, Inc

Epson Canada Limited 3840 Kilroy Airport Way, Long Beach, CA 90806 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

Specifications and terms are subject to change without notice. EPSON and ESC/POS are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. Mobilink is a trademark of Epson America. Inc. Android is a trademark of Google Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2016 Epson America, Inc. Com-SS-Oct-13 CPD-52085 7/16