

EXCLUSIVE OFFER...
POWER AHEAD — FOR LESS!



FULLY RUGGED 60 WATT USBC POWER ADAPTER

POWER THAT PULLS ITS WEIGHT

Don't let the size fool you — the Lind 60 Watt USB-C Power Adapter packs a serious punch. Designed for going anywhere the job takes you, this compact charger is ready to keep your devices powered up whether you're in a patrol car, a service truck, or somewhere off the beaten path. Offered in a universal design that is compatible with any USB-C device or cradle requiring up to 60W of power like a USB-C laptop, tablet, camera or phone — this little workhorse delivers fast, reliable power in a rugged package for years of use.

For the first time ever, Lind is offering special promotional pricing*. Check out our full lineup of rugged power solutions at LindElectronics.com.



STANDARD MODELS (ADDITIONAL CONFIGURATIONS AVAILABLE UPON REQUEST)

USBC-4901 - 11-16VDC Input Voltage
36" cig plug input cable

USBC-4815 - 11-32VDC Input Voltage
36" cig plug input cable

USBC-4979 - 11-16VDC Input Voltage
36" bare wire input cable

USBC-4973 - 11-32VDC Input Voltage
36" bare wire input cable

LIND

FEATURES

- ✓ Low Input Voltage Cut Off (LIVCO)
- ✓ 10-sec LIVCO delay
- ✓ High Input Voltage Cut Off
- ✓ Output Overcurrent Protection
- ✓ Internal Over Temperature Protection
- ✓ VBUS to CC short protection
- ✓ High Output Voltage Limit
- ✓ Automatic Restart of Adapter
- ✓ ESD protection on VBUS, CC lines
- ✓ Supports USB PD 2.0 Charging Protocol with Standard Profiles

TECHNICAL SPECS

- ⚡ INPUT VOLTAGE:
11-16 or 11-32 VDC
- ⚡ OUTPUT VOLTAGES:
5V, 9V, 15V and 20V
- ⚡ TOTAL LOAD CURRENT: 3.0A
- ⚡ OUTPUT VOLTAGE RIPPLE:
150mV at 100W load
- ⚡ WEIGHT: 255 gram (excluding cables)
- ⚡ DIMENSIONS: 123 x 58 x 29 mm
- ⚡ OPERATING TEMP: -20 to +40° C
- ⚡ STORAGE TEMP: -40 to +85° C

*Terms:

No minimums required. While supplies last.
Offer not valid with prior purchases.

