



Performance & Technical Specifications

PERFORMANCE	Model Number	CSUV-UG6CX
	Sanitation Cycle	20 Seconds
	Power ON	24/7
PHYSICAL DIMENSION	Lid Closed	L 26.7" x W 16.5" x H 12.3" (L 68cm x W 42cm x H 31.3cm)
	Lid Open	L 26.7" x W 16.5" x H 21.2" (L 68cm x W 42cm x H 53.9cm)
	Weight / Desktop Footprint	37lb (17kg) / 15.7" x 16.45" (40 x 42cm)
	Tray Dimensions	L 9.4" x W 12.87" x H 3.45" (L 24cm x W 32.7cm x H 8.8cm)
ENVIRONMENTAL	Operating Temperature	5° C / 41° F to 40° C / 104° F
	Humidity	50% @ 40° C / 104° F - 81% @ 31° C / 88° F
	Noise	< 35dB
	Pressure	Atmospheric (101.3 kPa)
ELECTRICAL	Voltage	120 / 240VAC, 50/60Hz
	Power Consumption - Idle	100W (idle), 130W (cycle)
	Fuse	5 x 20mm 3A 250V
BULBS	Germicidal UV-C bulbs	Six (three upper and three lower)
USER INTERFACE	Lid Open	Automatic
	Lid Contact Surface	Vinyl silver sheet
	Touch Screen	Yes
	Cycle Abort (Stop Button)	Yes
MISCELLANEOUS	Initial Warm-up time	60 Seconds
REGULATORY	Electrical Safety	IEC 61010-1
	Emission (EMI/EMC)	Class A limits of IEC 61326, FCC Part 15 Subpart B and ICES-003
	Wireless Transmitter	FCC and CE certified
	CE Marking	Yes
	RoHS Compliant	Yes

CANADA

800 Steeles Ave. W,
#B10182
Thornhill, ON, L4J 7L2

USA

2240 Lane Ave. North,
Suite 106
Jacksonville, FL 32254

cleanslateuv.com

sales@cleanslateuv.com
+ 1 877 553 6778