

## SEAL CLEAN™ WATERPROOF KEYBOARD

**Model:** SSKSV207, SSWKSV207,  
SSKSV207L, SSWKSV207L

Seal Clean Waterproof Keyboards from Seal Shield™. 100% waterproof & dishwasher-safe keyboard is IPX8-certified and designed to withstand industrial-grade disinfectants & cleaners. True type keyboard with tactile feel and full travel keys for smooth and natural typing. Features a Quick Connect or Long Cable with RF shielding and a Seal Cap™ for easy plug-and-play. Full-Size numeric keypad and Laser-etched keycaps enhance durability and product longevity throughout regular and vigorous cleaning.

### FEATURES:



100% Waterproof,  
Dishwasher-Safe,  
& Fully Submersible



IPX8-Certified



Full-Size Numeric  
Keypad and  
Laser Etched Keycaps



Gold Coated USB  
with Seal Cap™ USB  
Protector



Cable Options Quick  
Connect or Long Cable  
with RF Shielding



Designed to Withstand  
Industrial-Grade  
Disinfectants & Cleaners



Standard Style Keyboard  
for Smooth Typing



ABS Plastic with  
Stainless Steel Screws &  
Non-Corrosive Components



SSKSV207



SSWKSV207



SSKSV207L



SSWKSV207L

### ADVANCED CLEANING CAPABILITIES

- Dishwasher-Safe
- Compatible with Spray & Wipe Disinfectant Products:
  - Clorox Healthcare®
  - Lysol®
  - PDI Products
  - Bleach, Ethanol, IPA, Quats, Citric Acid, & Hydrogen Peroxide, and Other Industrial-Grade Cleaners and Disinfectants



**SEAL CLEAN™ WATERPROOF KEYBOARD****Model:** SSKSV207, SSWKSV207, SSKSV207L, SSWKSV207L**TECHNICAL DATA:**

Compatibility:	Windows® 10 Version 1803 x64
Construction:	ABS Plastic (Standard Style)
Net Dimensions L x W x H:	18.07 x 6.85 x 1.38 in (45.9 x 17.4 x 3.5 cm)
Key Layout:	104 US Language
Net Weight:	207: 1.93 lb (0.875 kg) 207L: 1.87 lb (0.850 kg)
Gross Weight:	207: 2.31 lb (1.050 kg) 207L: 2.26 lb (1.025 kg)
Cable Length:	SSKSV207L, SSWKSV207L: 6 ft.(1.83m) USB Extension Cable SSKSV207, SSWKSV207: 6in (15cm) Quick Connect Cable with 6 ft.(1.83m) USB Extension Cable
Connection Type:	Gold Plated USB (can support PS/2 technology)
Key Switch Force:	53 ± 7 gf
Key Switch Life Cycle:	Greater Than 10 Million Keystrokes
Key Switch Type:	Membrane Key Switch with Tactile Feedback
Keycaps Imaging Type:	Laser Etched
Total Key Travel:	4.0 ± 0.2mm
Operating Current:	60mA
Operating Voltage:	5VDC
Storage Temperature & Humidity:	High Temperature: 65°C, Humidity 95% time 96 hours Low Temperature: -20°C, Humidity 0% time 96 hours
Operating Temperature & Humidity:	High Temperature: 60+2°C, Humidity 90% time 96 hours Low Temperature: -20+2°C, Humidity 0% time 96 hours
EMI - RFI:	Conforms to FCC Rules for Class B Computing Device
Waterproof/Dustproof Ratings:	IPX8, NEMA 4X
Approvals/Certifications:	FCC, CE, RoHS, WEEE, WHQL, ICES-003, EAC, BIS, KC, RCM, and cULus, REACH, Cal Prop 65



Copyright© 2024, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners.

Limited 2-Year Warranty