EPSON®

EXCEED YOUR VISION

TM-U675 Multifunction Teller Printer

Compact multifunction printer with MICR for financial institutions.

Full-featured — all in a small footprint; ideal for teller stations

Versatile paper handling — easy drop-in loading and 1-touch removal; supports 90-degree print rotation

Superior slip handling — built-in forms stopper for extra stability

Fast — high-speed MICR reading and check printing

User-friendly design — wide throat for quick, smooth drop-in validation

Remarkable reliability — Automatic Status Back function for status updates and built-in maintenance counter for scheduling routine maintenance; MCBF of 37 million lines[1]

Integration made easy — RS-232C, bi-directional Parallel, RS-485 and USB interfaces

Industry-leading service and support — 1-year limited warranty

Whisper-quiet — ultra quiet printing for unobtrusive operation

---

General

Print Method 9-pin, serial impact dot matrix

Print Font
Font: 5 x 9 / 7 x 9
Column Capacity:
37 / 50 columns (Receipt), 45 / 60 columns (Slip/Validation)
Character Size:
1.56 mm x 3.1 mm (W x H) / 1.24 mm x 3.1 mm (W x H);
[0.061" x 0.122"/0.049" x 0.122"]
Character Set:
95 Alphanumeric, 37 International, 128 x 11
Graphic characters

Printer

Interfaces RS-232C / Bi-directional Parallel / RS-485 / USB / Connect-It™2

Data Buffer 4KB or 45 bytes

Print Speed Approx. 5.14 lines per second
[40 columns, 17.8 characters per inch (characters per 25.4 mm)]

Paper Dimensions
Receipts or Journal: 82.5 mm ± 0.5 mm x diameter 83 mm (3.25" ± 0.02" x diameter 3.27")
Slip: 70 mm to 148 mm x 150 mm to 210 mm (W x L) (2.76" to 5.83" x 5.91" to 8.27")
Validation: 148 mm to 150 mm x 70 mm to 210 mm (W x L) (5.83" to 5.91" x 2.76" to 8.27")

Paper Thickness
Receipts or Journal: 0.06 mm to 0.085 mm (0.0024" to 0.0033") / sheet [total thickness: 0.2 mm (0.0079") or less]
Slip: 0.09 mm to 0.2 mm (0.0035" to 0.0079") / sheet (total thickness: 0.09 mm to 0.31 mm) [0.0035" to 0.0122"]

Printer (continued)

Validation 8 lines

Copy Capability 1 original and 2 copies

Inked Ribbon ERC-32

Ribbon Life 4,000,000 characters

Power Supply 24 VDC ± 10%

Power Consumption Approx. 1.7 A (mean)

D.K.D. Function 2 drivers

Reliability
MTBF: 180,000 hours
MCBF: 37,000,000 lines

Overall Dimensions (W x D x H)
186 mm x 298 mm x 195 mm [7.3" x 11.7" x 7.7"]

Mass
Approx. 4.8 kg (10.6 lb)
With auto cutter: Approx. 5.8 kg (12.8 lb)

NV Bit Image Memory 384 KB can be used to store graphic files

Factory Options Auto cutter, MICR

Control Board

EMI Standards VCCI class A, FCC class A, CE marking

Safety Standards UL, CSA

Eco Features

RoHS compliant
Recyclable product[3]
Epson America, Inc. is a SmartWay® Transport Partner[4]
Inch values are approximate.

Ordering Information

Model Number	Part Number
TM-U675-032: EDG; U03II; NO MICR; AUTO CUTR	C31C283A8711
TM-U675-082: EDG; UB-U03II; NO MICR; NO A/C	C31C283A8771
TM-U675-082: EDG; SERIAL; NO MICR; NO A/C	C31C283A8911
TM-U675-012: BX (ECW); NO MICR; SRL; (B) RBN	C31C283012
TM-U675-083: ECW; NO MICR; W/O A/C; UB-U03II	C31C283A8901

For additional connectivity options, please contact your Epson representative.

See the latest innovations from Epson Business Solutions at **www.epson.com/forbusiness**

Better Products for a Better Future™
eco.epson.com

SmartWay®
Transport Partner
Getting There With Cleaner Air

ENERGY STAR

Contact:

Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited
185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca